

ACMI #1400
Continuous Stream
JET PRINTING INK
NONPOROUS

Description:

ACMI #1400 was formulated for use in high speed, electrostatically deflected, continuous droplet jet printers. This ink dries instantly and produces high resolution character printing on virtually any nonporous substrate.

SPECIFICATIONS:

<u>Applications:</u>	Continuous Stream jet printers on nonporous substrates such as glass, ceramic and metal containers
<u>Viscosity:</u>	4 cps
<u>Specific Gravity:</u>	0.86
<u>Weight per Gallon:</u>	7.17 lbs.
<u>Flashpoint:</u>	28° F.
<u>Dry time:</u>	10 seconds Variations in temperature and humidity may affect dry time.
<u>Shelf Life & Storage:</u>	Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.
<u>Chemical Base:</u>	Solvent (MEK)
<u>Colorant Base:</u>	Dye
<u>RECONDITIONER:</u>	#1420 Reconditioner AKA: Make-up ink
<u>CLEANER:</u>	#1440 Cleaner
<u>COLORS:</u>	Black, Violet, Red, Blue, Green, Yellow, Invisible
<u>AVAILABILITY:</u>	Pints, Quarts and Gallons

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

American Coding and Marking Ink Co. Inc.

1220 North Avenue, Plainfield, NJ 07062

Phone: 908-756-0373 **Fax:** 908-756-0570 **Web Site:** www.americancoding.com