

**ACMI #2610**  
**ALCOHOL**  
**RESISTANT**  
**NONPOROUS**

Description: ACMI #2610 was formulated as a fast drying, alcohol resistant ink for rubber stamp marking on nonporous substrates. This ink has been found to resist wave solder and flux remover, as well as high temperature for short periods of time and is non-conductive. #2610 has been used successfully on PC board.

**SPECIFICATIONS:**

Applications: Rubber stamp marking on nonporous substrates.  
Cloth covered felt stamp pad is preferred.

Viscosity: 20 cps

Specific Gravity: 1.0

Weight per Gallon: 8.4 lbs.

Flashpoint: 65° F.

Dry time: 3 minutes  
Variations in temperature and humidity may affect dry time.

Shelf Life & Storage: Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.

Chemical Base: Solvent

Colorant Base: Pigment

**RECONDITIONER:** #2610 Reconditioner

**COLORS:** Black, White

**AVAILABILITY:** Pints, Quarts and Gallons  
Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

***American Coding and Marking Ink Co. Inc.***

1220 North Avenue, Plainfield, NJ 07062

**Phone:** 908-756-0373 **Fax:** 908-756-0570 **Web Site:** [www.americancoding.com](http://www.americancoding.com)