

ACMI #700
NON-POROUS
STAMP PAD INK
BOTTOM CODING

ACMI #700 was formulated for rubber stamp marking plastics, metals, glass, film, foil and other nonporous substrates from a stamp pad. #700 is also used for bottom coding on aerosol containers and small plastic, glass and metal non-aerosol containers with the use of an inline high speed automatic machine. This ink dries fast and is able to print through moisture.

SPECIFICATIONS:

Applications: Rubber stamp with cloth covered stamp pad, flexographic printer, air sprayer, inline high speed automatic machine for bottom coding.

Viscosity: 27 cps

Specific Gravity: 0.95 1.07 1.10

Weight per Gallon: 7.92lbs. 8.92lbs. 9.17lbs.

Flashpoint: 90° F. -108° F. depending on color

Dry time: 45-60 seconds

Variations in temperature and humidity may affect dry time.

Shelf Life & Storage: Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.

Chemical Base: Solvent

Colorant Base: Dye

RECONDITIONER: #700 Reconditioner

COLORS: Black, White, Violet, Red, Blue, Green, Yellow, Orange

AVAILABILITY: Pints, Quarts and Gallons
Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

American Coding and Marking Ink Co. Inc.

1220 North Avenue, Plainfield, NJ 07062

Phone: 908-756-0373 Fax: 908-756-0570 Web Site: www.americancoding.com