

ACMI #528
INVISIBLE
POROUS
SUBSTRATES

Description:

ACMI #528 is a slower drying version of #508 invisible ink for use on porous substrates only. This ink may be applied by rubber stamp. It is designed to fluoresce blue at 380nm under ultraviolet light.

SPECIFICATIONS:

<u>Applications:</u>	Rubber stamp on porous substrates only For applications which require extended pad life
<u>Viscosity:</u>	10 cps
<u>Specific Gravity:</u>	1.10
<u>Weight per Gallon:</u>	9.17 lbs.
<u>Flashpoint:</u>	116° F.
<u>Dry time:</u>	Medium Fast Variations in temperature and humidity may affect dry time.
<u>Shelf Life & Storage:</u>	Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.
<u>Chemical Base:</u>	Solvent
<u>Colorant Base:</u>	Dye
<u>RECONDITIONER:</u>	#528 Reconditioner
<u>COLORS:</u>	Invisible - Fluoresces blue under ultraviolet light
<u>AVAILABILITY:</u>	Pints, Quarts and Gallons Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

American Coding and Marking Ink Co. Inc.

1220 North Avenue, Plainfield, NJ 07062

Phone: 908-756-0373 **Fax:** 908-756-0570 **Web Site:** www.americancoding.com